

HIGH PRESSURE OIL SEPARATOR VESSEL RECIPIENTE SEPARADOR DE ACEITE DE ALTA PRESIÓN

32bar -20/100°C				Kg	V (L)				Dimensions Dimensiones (mm)						Maximum Capacity Capacidad Máxima Kw TCond			
					Va	Vt	Vv1	Vv2	Ø	Hout	Hr	Hv1	Hv2	H	R134a		R404A	
															-30°C	+5°C	-40°C	+5°C
CAT. II	SAV-3,5	7/8"	53.001	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546	28	30	36	45
CAT. II	SAV-3,5	1 1/8"	53.002	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546	35	41	52	60
CAT. II	SAV-3,5	1 3/8"	53.003	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546	40	50	60	70
CAT. II	SAV-9,5	1 3/8"	53.004	17	9.5	17	2,9	5,6	193	584	121	155	255	732	60	80	80	120
CAT. II	SAV-9,5	1 5/8"	53.005	17	9.5	17	2,9	5,6	193	584	121	155	255	732	85	100	110	160
CAT. II	SAV-9,5	2 1/8"	53.006	17	9.5	17	2,9	5,6	193	584	121	155	255	732	90	100	145	165
CAT. III	SAV-20	2 1/8"	53.007	25	20	31	5,5	12	273	512	170	170	288	773	120	152	170	252
CAT. III	SAV-20	2 5/8"	53.008	25	20	31	5,5	12	273	512	170	170	288	773	158	180	268	300
CAT. III	SAV-20	3 1/8"	53.009	25	20	31	5,5	12	273	512	170	170	288	773	158	180	268	300

VALID FOR ALL THE REFRIGERANTS HFC: / VÁLIDO PARA TODOS LOS REFRIGERANTES HFC: R22, R134a, R404A, R507,ETC

All models include rotalock valve 1"x 3/8" SAE in oil outlet connections

Todos los modelos incluyen válvula rotalock 1" x 3/8" SAE en la conexión de salida de aceite.



HIGH PRESSURE OIL SEPARATOR VESSEL RECIPIENTE SEPARADOR DE ACEITE DE ALTA PRESIÓN

NH ₃ 32bar -20/100°C				Kg	V(L)				Dimensions/Dimensiones (mm)					
					Va	Vt	Vv1	Vv2	Ø	Hout	Hr	Hv1	Hv2	H
CAT. II	SAV-3,5-NH ₃	7/8"	53.019	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-3,5-NH ₃	1 1/8"	53.020	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-3,5-NH ₃	1 3/8"	53.021	8.5	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-9,5-NH ₃	1 3/8"	53.022	17	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. II	SAV-9,5-NH ₃	1 5/8"	53.023	17	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. II	SAV-9,5-NH ₃	2 1/8"	53.024	17	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. III	SAV-20-NH ₂	2 1/8"	53.025	25	20	31	5,5	12	273	512	170	170	288	773
CAT. III	SAV-20-NH ₃	2 5/8"	53.026	25	20	31	5,5	12	273	512	170	170	288	773
CAT. III	SAV-20-NH ₃	3 1/8"	53.027	25	20	31	5,5	12	273	512	170	170	288	773

All models include rotalock adapter 1"x 3/8" ODS in oil outlet connections

Todos los modelos incluyen adaptador rotalock 1" x 3/8" ODS en la conexión de salida de aceite.



HIGH PRESSURE OIL SEPARATOR VESSEL FOR CO₂ (Subcritical) RECIPIENTE SEPARADOR DE ACEITE DE ALTA PRESIÓN PARA CO₂

R410A

CO ₂ 45bar -10/100°C (Subcritical)				Kg	V (L)				Dimensions Dimensiones (mm)					
					Va	Vt	Vv1	Vv2	Ø	Hout	Hr	Hv1	Hv2	H
CAT. II	SAV-3,5/45	7/8"	53.010	10	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-3,5/45	1 1/8"	53.011	10	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-3,5/45	1 3/8"	53.012	10	3.5	9	0,9	2,1	159	426	72	75	132	546
CAT. II	SAV-9,5/45	1 3/8"	53.013	19	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. II	SAV-9,5/45	1 5/8"	53.014	19	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. II	SAV-9,5/45	2 1/8"	53.015	19	9.5	17	2,9	5,6	193	584	121	155	255	732
CAT. III	SAV-20/45	2 1/8"	53.016	28	20	31	5,5	12	273	512	170	170	288	773
CAT. III	SAV-20/45	2 5/8"	53.017	28	20	31	5,5	12	273	512	170	170	288	773
CAT. III	SAV-20/45	3 1/8"	53.018	28	20	31	5,5	12	273	512	170	170	288	773

All models include rotalock valve 1"x 3/8" SAE in oil outlet connections

Todos los modelos incluyen válvula rotalock 1" x 3/8" SAE en la conexión de salida de aceite.



Va : Oil Separator Volume

Volumen Separador de aceite

Vt : Va + Oil Receiver Volume.

Va+ Volumen Recipiente de aceite

**OPTIONAL / OPCIONAL:
SPECIAL PAINTING FOR CO₂
PINTURA ESPECIAL PARA CO₂
400 µm
(recommended / recomendada)**

