

31 bar -10/120°C 10 bar -20/100°C			Kg	Type	Va (L)	Vt (L)	Dimensions Dimensiones (mm)				Capacity Capacidad Kw			
							R134a		R404A/507					
							D	H	H1	H2	-25°C	+5°C	-40°C	+5°C
CAT. I	SAC-1 7/8"	89.001	18	a	1.5	3	102	450	150	388	13.7	23.3	11.9	36.1
CAT. I	SAC-2 1 1/8"	89.002	19	a	1.6	4	102	550	150	485	22.9	39.8	18.3	61.8
CAT. I	SAC-3 1 3/8"	89.003	19	a	1.6	4	102	550	150	485	35.1	58.2	29.3	90.3
CAT. II	SAC-4 1 5/8"	89.004	46	b	3.5	13	159	860	295	770	58.1	102.9	47.6	173.1
CAT. II	SAC-5 2 1/8"	89.005	46.5	b	3.5	13	159	860	295	765	85.6	140.9	65.9	218.7
CAT. I II	SAC-6 2 5/8"	89.006	80	b	17.2	50	273	1222	408	1075	92.3	191	77.6	296.7
CAT. III	SAC-7 3 1/8"	89.007	81	b	17.2	50	273	1222	408	1075	119.3	278.6	105	432.6
CAT. III	new SAC-8 3 1/8"	89.022	84	b	22.3	65	273	1450	408	1303	125	280	109	435

VALID FOR ALL THE REFRIGERANTS HFC: R22, R134a, R404A, R507,ETC

VÁLIDO PARA TODOS LOS REFRIGERANTES HFC: R22, R134a, R404A, R507,ETC

NH₃ COALESCENT OIL SEPARATORS
SEPARADORES DE ACEITE COALESCENTES PARA NH₃

NH ₃ 31 bar -10/120°C 10 bar -20/100°C			Kg	Type	Va (L)	Vt (L)	Dimensions Dimensiones (mm)				KW (T ^a cond. 37.8°C; supercalen. 5.6°C; Subenfr. 0°C)	
							D	H	H1	H2	+4.4°C	-40°C
							CAT. II	SAC-4 -NH ₃ 1 5/8"	89.011	46	b	3.5
CAT. II	SAC-5 -NH ₃ 2 1/8"	89.012	46.5	b	3.5	13	159	860	295	765	310	47
CAT. III	SAC-6 -NH ₃ 2 5/8"	89.013	80	b	17.2	50	273	1222	408	1075	512	77
CAT. III	SAC-7 -NH ₃ 3 1/8"	89.014	81	b	17.2	50	273	1222	408	1075	874	132
CAT. III	new SAC-8 -NH ₃ 3 1/8"	89.023	84	b	22.3	65	273	1450	408	1303	880	135

COALESCENT OIL SEPARATORS FOR CO₂ (Subcritical)
SEPARADORES DE ACEITE COALESCENTES PARA CO₂ (Subcrítico)

R410A

CO ₂ 45 bar -10/120°C 10 bar -20/100°C			Kg	Type	Va (L)	Vt (L)	Dimensions Dimensiones (mm)				FOR CO ₂ KW (T ^a cond. -3.88°C; supercalen. 5.6°C; Subenfr. 0°C)	
							D	H	H1	H2	+4.4°C	-40°C
							CAT. I	SAC-1 - 45 7/8"	89.015	19	a	1.5
CAT. I	SAC-2 - 45 1 1/8"	89.016	21	a	1.6	4	102	550	150	485	258	62
CAT. I	SAC-3 - 45 1 3/8"	89.017	21	a	1.6	4	102	550	150	485	393	95.5
CAT. II	SAC-4 - 45 1 5/8"	89.018	50	b	3.5	13	159	860	295	770	673	163.7
CAT. II	SAC-5 - 45 2 1/8"	89.019	50	b	3.5	13	159	860	295	765	918	222
CAT. I II	SAC-6 - 45 2 5/8"	89.020	95	b	17.2	50	273	1222	408	1075	1534,5	373,4
CAT. III	SAC-7 - 45 3 1/8"	89.021	96	b	17.2	50	273	1222	408	1075	2610	634,9
CAT. III	new SAC-8 - 45 3 1/8"	89.024	100	b	22.3	65	273	1450	408	1303	2612	640

OPTIONAL / OPCIONAL:
SPECIAL PAINTING FOR CO₂
PINTURA ESPECIAL PARA CO₂
400 µm
(recommended / recomendada)

ALL THE MODELS ARE PAINTED IN BLACK
TODOS LOS MODELOS SON PINTADOS EN NEGRO

