

31 bar -10/120°C 10 bar -20/100°C				Kg	Type	Vs (L)	Vr (L)	Vt (L)	Dimensions Dimensiones(mm)					Capacity Capacidad Kw			
									Dimensions Dimensiones (mm)					R134a		R404A/507	
									D	H	h	H1	H2	-25°C	+5°C	-40°C	+5°C
CAT. I	SARC-1	7/8"	93.001	15.5	a	1.5	2.5	4	102	550	65	250	485	13.7	23.3	11.9	36.1
CAT. I	SARC-2	1 1/8"	93.002	16.5	b	2.3	2.7	5	102	830	110	425	765	22.9	39.8	18.3	61.8
CAT. I	SARC-3	1 3/8"	93.003	16.5	b	2.3	2.7	5	102	830	110	425	765	35.1	58.2	29.3	90.3
CAT. II	SARC-4	1 5/8"	93.004	43.5	b	8	8	16	159	980	110	420	890	58.1	102.9	47.6	173.1
CAT. II	SARC-5	2 1/8"	93.005	43.5	b	8	8	16	159	980	110	420	885	85.6	140.9	65.9	218.7
CAT. I II	SARC-6	2 5/8"	93.006	77.5	b	35	24	59	273	1200	185	383	1050	92.3	191	77.6	296.7
CAT. III	SARC-7	3 1/8"	93.007	78.5	b	35	24	59	273	1200	185	383	1050	119.3	278.6	105	432.6
CAT. III	new SARC-8	3 1/8"	93.022	81	b	44	30	74	273	1428	185	383	1278	122	280	115	438

VALID FOR ALL THE REFRIGERANTS HFC: R22, R134a, R404A, R507,ETC

VÁLIDO PARA TODOS LOS REFRIGERANTES HFC: R22, R134a, R404A, R507,ETC

NH₃ COALESCENT OIL SEPARATORS WITH OIL RECEIVER
SEPARADORES DE ACEITE COALESCENTES CON RECIPIENTE DE ACEITE PARA NH₃

NH ₃ 31 bar -10/120°C 10 bar -20/100°C				Kg	Type	Vs (L)	Vr (L)	Vt (L)	Dimensions Dimensiones (mm)					KW (T ^o cond. 37.8°C; supercalen. 5.6°C; Subenfr. 0°C)	
Dimensions Dimensiones (mm)									+4.4°C	-40°C					
D	H	h	H1						H2						
CAT. I	SARC-1 -NH ₃	7/8"	93.008	15.5	a	1.5	2.5	4	102	550	65	250	485	48	7,4
CAT. I	SARC-2 -NH ₃	1 1/8"	93.009	16.5	b	2.3	2.7	5	102	830	110	425	765	87	12,5
CAT. I	SARC-3 -NH ₃	1 3/8"	9.010	16.5	b	2.3	2.7	5	102	830	110	425	765	130	19,8
CAT. II	SARC-4 -NH ₃	1 5/8"	93.011	43.5	b	8	8	16	159	980	110	420	890	225	35
CAT. II	SARC-5 -NH ₃	2 1/8"	93.012	43.5	b	8	8	16	159	980	110	420	885	310	47
CAT. I II	SARC-6 -NH ₃	2 5/8"	93.013	77.5	b	35	24	59	273	1200	185	383	1050	512	77
CAT. III	SARC-7 -NH ₃	3 1/8"	93.014	78.5	b	35	24	59	273	1200	185	383	1050	874	132
CAT. III	new SARC-8-NH ₃	3 1/8"	93.023	81	b	44	30	74	273	1428	185	383	1278	880	135

CO₂ COALESCENT OIL SEPARATORS WITH OIL RECEIVER (Subcritical)
SEPARADORES DE ACEITE COALESCENTES CON RECIPIENTE DE ACEITE PARA CO₂

R410A

CO ₂ 45 bar -10/120°C 10 bar -20/100°C				Kg	Type	Vs (L)	Vr (L)	Vt (L)	Dimensions Dimensiones (mm)					FOR CO ₂ KW (T ^o cond. -3,88°C; supercalen. 5.6°C; Subenfr. 0°C)	
Dimensions Dimensiones (mm)									+4.4°C	-40°C					
D	H	h	H1						H2						
CAT. I	SARC-1 -45	7/8"	93.015	16.5	a	1.5	2.5	4	102	550	65	250	485	141	34
CAT. I	SARC-2 -45	1 1/8"	93.016	18	b	2.3	2.7	5	102	830	110	425	765	258	62
CAT. I	SARC-3 -45	1 3/8"	93.017	18	b	2.3	2.7	5	102	830	110	425	765	393	95,5
CAT. II	SARC-4 -45	1 5/8"	93.018	47	b	8	8	16	159	980	110	420	890	673	163,7
CAT. II	SARC-5 -45	2 1/8"	93.019	47	b	8	8	16	159	980	110	420	885	918	222
CAT. I II	SARC-6 -45	2 5/8"	93.020	92	b	35	24	59	273	1200	185	383	1050	1534,5	373,4
CAT. III	SARC-7 -45	3 1/8"	93.021	93	b	35	24	59	273	1200	185	383	1050	2610	634,9
CAT. III	new SARC-8-45	3 1/8"	93.024	97	b	44	30	74	273	1428	185	383	1278	2612	640

Vs: Volume Oil Separator / Volumen separador de aceite
Vr: Volume Oil Receiver / Volumen Recipiente de Aceite

OPTIONAL / OPCIONAL:
SPECIAL PAINTING FOR CO₂
PINTURA ESPECIAL PARA CO₂
400 µm
(recommended / recomendada)

ALL THE MODELS ARE PAINTED IN BLACK
TODOS LOS MODELOS SON PINTADOS EN NEGRO

